

TOPAIRE

AIR CONDITIONERS

Slim Floor

STANDING



Innovation Beyond Comfort



TAS 25EG / TAS 30FS



TAS 50FS



TFS 30E / TFS 50E



Operating Mode

- 4 function mode [Auto, cooling, Drying (dehumidification) and fan only]



Fan Speed Adjustmet

- Fan speed mode [Auto, low, High]



Automatic Swing

- Auto up /down and left / right swing



On/Off Power By Manual or (Auto Restart)



LED Display

- LED room temperature setting digital display

Specifications

MODEL	OUTDOOR	TAS 25 EG	TAS 30 FS	TAS 50 FS
	INDOOR	TFS 30 E	TFS 30 E	TFS 50 E
NOMINAL CAPACITY	BTU/HR	25,000	30,000	50,000
	KW	7.33	8.79	14.65
POWER SUPPLY	V/PH/HZ	240 / 1 / 50		
INDOOR FEATURES				
FAN				
SOUND LEVEL	dBA	45	45	48
AIR FLOW	CFM	860	860	1260
RATED POWER INPUT	WATT	132	132	340
RATED AMPERE	A	0.7	0.7	1.8
TYPE	CENTRIFUGAL FAN / DIRECT DRIVE			
EVAPORATOR COIL				
TUBE	SEAMLESS INNER GROOVE COPPER TUBE			
FIN	ANTI CORROSION HYDROPHILIC ALUMINUM SLIT FIN			
CONTROL				
ROOM TEMPERATURE	MICROCOMPUTER WIRELESS CONTROLLER THERMOSTAT			
CONTROL DISPLAY	LCD DISPLAY SCREEN			
AIR DISCHARGE	AUTO SWING LOUVER (LEFT / RIGHT) & MANUAL (UP / DOWN)			
OPERATION	LCD DISPLAY SCREEN C/W FLUORESCENCE BUTTON & AUTO RESTART			
TIMER	24 HOUR - ON / OFF TIMER			
AIR FILTER	WASHABLE SARAN NET			
DIMENSION				
WIDTH	MM	500	500	540
DEPTH	MM	273	273	370
HEIGHT	MM	1670	1670	1780
NET WEIGHT	KG	46	46	56
OUTDOOR FEATURES				
COMPRESSOR				
POWER SUPPLY	V/PH/HZ	240 / 1 / 50	240 / 1 / 50	415 / 3 / 50
RATED POWER INPUT	WATT	2380	3000	4660
RATED AMPERE	A	11.5	13.0	8.6
TYPE	ROTARY HERMETIC			
PROTECTION DEVICE	THERMAL OVERLOAD			
	SCROLL HERMETIC			
	AUTO RESET HI-LO			
	PRESSURE SWITCH			
FAN				
TYPE	PROPELLER FAN / DIRECT DRIVE			
RATED POWER INPUT	WATT	140	168	307
RATED AMPERE	A	0.72	0.74	1.70
CONDENSER COIL				
TUBE	SEAMLESS INNER GROOVE COPPER TUBE			
FIN	ALUMINUM SLIT FIN			
REFRIGERANT	R - 22			
CAPACITY CONTROL	CAPILLARY AT OUTDOOR		CAPILLARY AT INDOOR	
CASING				
MATERIAL	ELECTRO-GALVANIZED MILD STEEL			
FINISH	EPOXY POWDER COATING			
PIPE				
DISCHARGE	MM / (IN)	9.25 (3/8)	9.25 (3/8)	12.7 (1/2)
SUCTION	MM / (IN)	15.88 (5/8)	15.88 (5/8)	19.0 (3/4)
DIMENSION				
WIDTH	MM	845	845	990
DEPTH	MM	335	335	350
HEIGHT	MM	695	695	960
NET WEIGHT	KG	56	67	90

All specifications are subject to change by manufacturer without prior notice.

Note : The nominal cooling capacity is based on condenser outdoor air entering temp. 35 °C (DB); indoor on coil temp. 27/19 °C (DB / WB)



TOPAIRE Sales & Services Sdn Bhd

(274725-W)

Lot 8, Jalan P/7, Sek. 13, P.O. Box 17, Kawasan Perusahaan Bangi
43650 Bandar Baru Bangi, Selangor Darul Ehsan, West Malaysia
T: 03-8925 2022 | F: 03-8925 5605 | E: tass@topairesales.com.my

Website: www.topaire.com.my

